

Hose Reel 888

Medium sized open hose reel.



Hose Reel 888

- ✔ Outlet position can be adjusted through 120° for optimum pull-out and pull-in angle.
- ✔ Spring power can easily be adjusted from the outside.
- ✔ Ratchet easily disengaged when required.

Thanks to the open design, the reels are very easy to service, maintain and keep clean. Can be installed on wall or on the ceiling.

This content is protected under copyright law, furnished for informational use only, and subject to change without notice. © Nederman Holding AB

Nederman

Hose Reel 888

Hose Reel 888

Certifications	[ce]
[ProductMedia]	Compressed air, Water, Water high pressure, Oil, Food, [grease]

[ProductConnectionHoseLength]	1
Corrosion resistance	Standard
Electric/Spring driven	Spring

This content is protected under copyright law, furnished for informational use only, and subject to change without notice. © Nederman Holding AB

2026-09-25

3/8

Nederman

Hose Reel 888

Models

	Item no	Type of hose	Media	Delivered with hose	Colour	Distribution hose length (m)	Diameter, connection hose (mm)	Distribution hose diameter (mm)	Max working pressure (Mpa)	Weight (kg)	Max hose length
	30801088	E	Water	[With]	Black drum / Blue arm	10	12.5	12.5	2	16	
	30801888	G	Water high pressure	[With]	Black drum /	15	10	10	25	16	

	Item no	Type of hose	Media	Delivered with hose	Colour	Distribution hose length (m)	Diameter, connection hose (mm)	Distribution hose diameter (mm)	Max working pressure (Mpa)	Weight (kg)	Max hose length
					Blue arm						
	30804288	J	[grease]	[With]	Black drum / White arm	15	10	10	35	18	
	30804688	I	Oil	[With]	Black drum / White arm	10	12.5	12.5	7.5	16	
	30804888	J	[grease]	[With]	Black drum / White arm	15	6	6	35	16	
	30800888	B	Compressed air, Water	[With]	Black drum / Blue arm	10	12.5	12.5	1.5	16	
	30805088	J	[grease]	[With]	Black drum / White arm	10	10	10	35	14	
	30851088	B	Compressed air, Water	[With]	Black drum / White arm	15	12.5	10	1.5	11	
	30801688	I	Oil	[With]	Black drum / Blue arm	10	12.5	12.5	7.5	16	
	30802688	J	[grease]	[With]	Black drum / Blue arm	15	6	6	35	16	
	30800388		Compressed air, Water	[Without]	Black drum / Blue arm			10	1.5	11	15
	30800788		Compressed air, Water	[Without]	Black drum / Blue arm			12.5	1.5	11	10
	30801788	G	Water high pressure	[Without]	Black drum / Blue arm			10	25	11	15

This content is protected under copyright law, furnished for informational use only, and subject to change without notice. © Nederman Holding AB

2026-09-25

4/8



Hose Reel 888

Models

	Item no	Type of hose	Media	Delivered with hose	Colour	Distribution hose length (m)	Diameter, connection hose (mm)	Distribution hose diameter (mm)	Max working pressure (Mpa)	Weight (kg)	Max hose length
	30801588	I	Oil	[Without]	Black drum / Blue arm			12.5	7.5	11	10
	30802588	J	[grease]	[Without]	Black drum / Blue arm			6	35	11	15
	30800688	B	Compressed	[With]	Black	15	12.5	10	1.5	16	

	Item no	Type of hose	Media	Delivered with hose	Colour	Distribution hose length (m)	Diameter, connection hose (mm)	Distribution hose diameter (mm)	Max working pressure (Mpa)	Weight (kg)	Max hose length
			air, Water		drum / Blue arm						

Hose types

Hose type	[HoseSpecification]	[HoseTemperatureRange]	[HoseFittingDistribution]	[HoseFittingInlet]	[HoseConnectionDistribution]	[HoseConnectionInlet]
B	Cover in NBR/PVC and inner tube in NBR. Syntethic textile braid	-30 - 100	Male, chrome plated		Hose nipple + clip	Hose nipple 1/2" + clip
E	Cover in NBR/PVC and inner tube in food grade quality NBR. Syntethic textile braid	-30 - 100	Male 60° cone, chrome plated	Female 60° cone, chrome plated	Male 60° cone	Male 60° cone
G	Cover and inner tube in synthetic rubber. Single steel braid	-40 - 155	Female 60° cone, chrome plated. With rubber hose grip	Female 60° cone, chrome plated	Male 60° cone	Male 60° cone
I	Cover and inner tube in SBR based rubber. Single steel braid	-40 - 100	Female 60° cone, chrome plated	Female 60° cone, chrome plated	Male 60° cone	Male 60° cone
J	Cover and inner tube in syntetic, oil resistant rubber. Double steel braid	-40 - 100	Female 60° cone, chrome plated	Female 60° cone, chrome plated	Male 60° cone	Male 60° cone

This content is protected under copyright law, furnished for informational use only, and subject to change without notice. © Nederman Holding AB

2026-09-25

5/8



Hose Reel 888

Accessories

	Accessory	Item no
	Roller guide.	30341550
	Pivoting bracket.	30372407
	Water gun in chromium plated brass. Max. temperature 95°C	30400110
	Water gun in stainless steel 316. Max. temperature 95°C	30400210

	Accessory	Item no
	Watergun EX	30400211
	Water gun in stainless steel 316. Max. temperature 95°C	30400310
	Air gun, standard.	30410110
	Swivelling coupling 3/8(m)-3/8(m)HP	30431310
	Swiv. coupling 3/8(m)-3/8(m) HP SS	30431410
	Swivl. coupl. 1/2(m)-3/8(f) brass	30431510
	Swivl. coupl. 1/2(m)-1/2(f) brass	30431610
	Swivel coupling 1/2(m)- 3/4 (f) bra	30431710
	Swivl. coupl. 1/2(m)-3/8(f) SS	30431810

This content is protected under copyright law, furnished for informational use only, and subject to change without notice. © Nederman Holding AB

2026-09-25

6/8

Nederman


Hose Reel 888

Accessories

	Accessory	Item no
	Swivl. coupl. 1/2(m)-1/2(f) SS	30431910
	Swivl. coupl. 1/2(m)-3/4(f) SS	30432010
	Inlet kit for hose reel 1/2"	30511550
	Inlet kit for hose reel 3/8" with ball valve 3/8", 3/8"-3/8" adapter and 1/4" - 3/8" adapter.	30511650

Nederman

Hose Reel 888



This content is protected under copyright law, furnished for informational use only, and subject to change without notice. © Nederman Holding AB

2026-09-25

8/8