Product leaflet

Industrial vacuum cleaner 115 E

Industrial dry vacuum cleaner for workshop cleaning

This content is protected under copyright law, furnished for informational use only, and subject to change without notice. © Nederman Holding AB

Industrial vacuum cleaner 115 E

- Versatile extractor
- Perfect for workshops

Electric powered industrial vacuum cleaner with a single container system, designed for the collection of dry or wet materials over short distances. Versatile vacuum for use in diverse industries and institutions. The vacuum suction equipment is light and easy to handle.

This content is protected under copyright law, furnished for informational use only, and subject to change without notice. © Nederman Holding AB

Industrial vacuum cleaner 115 E

Certifications	CE
Noise level (dB(A))	75
Installation	Indoor
Filter cleaning method	One way filter
Application	Dust, Liquid, Granulate, Swarf
Dustbin volume (l)	40
Max Airflow (m3/h)	460
Filter Area (m²)	0.35
Frequency (Hz)	50/60
No of phases	1
Filter type	Bag
Number of filter elements	1
Filter material	Polyester-Teflon
Max airflow (m³/h)	460
Noise level (dB(A))	75
Max vaccum (kPa)	-21,5
Weight (kg)	50
Power (kW)	2,4

This content is protected under copyright law, furnished for informational use only, and subject to change without notice. © Nederman Holding AB

Models

	Item no	Power Voltage (V)	Type of hose	Hose length (m)	Hose diameter (mm)
	42411582[1]	110	PE/C	7,5	51
	42411581[1]	230	PE/C	7,5	51
	42411501[2]	110	PVC	7,5	51
	42411580	230	PE/C	5	38

[1] With cleaning set
[2] With cleaning set, toothed and conical nozzle

Hose types

Hose type	Specification	Temperature range, °C	Hose fittings in free hose end, distribution hose	Hose fitting on free hose end, inlet hose	Hose connection on reel, distribution hose	Hose connection on reel, inlet hose
PVC	Max vacuum 84 kPA Inner bending radius 60 mm Reinforced with inbedded steel helix	- 20 deg. C. to + 70 Deg. C.				
PEC	For cleaning applications Max vacuum 50 kPa Conductivity 10^3 to 10^6 Ohm/m	-40°C - +60°C				

This content is protected under copyright law, furnished for informational use only, and subject to change without notice. © Nederman Holding AB