

Suction hose PE



Suction hose PE

- ✓ Temp. range: -40° to +60 °C.
- ✓ Max. vacuum 50 kPa.

Application areas: Single suction hose, mainly intended for simple cleaning. The hose is not conductive.

Suction hose PE

Standard	Designed for ISO 21904 compliance
----------	-----------------------------------

Models

	Item no	Max vacuum (kPa)	Diameter (mm)	length (m)
	40160712	50	25	10
	40160722	50	32	10
	40160731	50	38	5
	40160733	50	38	10
	40160735	50	38	20
	40160741	50	51	5
	40375953	50	32	5
	40160370		38	5
	40160380		50	5
	40160743	50	51	10
	40160745	50	51	20
	43812300			
	43812400			

Models

	Item no	Max vacuum (kPa)	Diameter (mm)	length (m)
	43812500			

Accessories

	Accessory	Item no
	Hose Shelf 30M 115x70	40195450
	Hose Shelf 60M 150x110	40195451
	Hose Shelf 120M 200x160	40195452
	Hose & Add.shelf	40196370
	Hose clamp 85	40903030
	Hose clamp 56	40903170
	Hose clamp 75	40903180
	Hose clamp 112	40903210
	Hose clamp 104-112 ABA Robust	40903270
	End sleeve PE d32	43819001
	End sleeve d38, pe	43819011