

PE 型抽排软管



PE 型抽排软管

- ✓ 温度范围: $-40^{\circ} \sim +60^{\circ} \text{C}$.
- ✓ 最大真空度 50 kPa.

应用领域: 单一抽排软管, 主要用于一般清洁。该软管不导电

PE 型抽排软管

标准	Designed for ISO 21904 compliance
----	-----------------------------------

模型

	项目编号	[ItemMaxVaccum]	直径 (mm)	[ItemLength]
	40160712	50	25	10
	40160722	50	32	10
	40160731	50	38	5
	40160733	50	38	10
	40160735	50	38	20
	40160741	50	51	5
	40375953	50	32	5
	40160370		38	5
	40160380		50	5
	40160745	50	51	20
	43812300			
	43812400			
	43812500			

配件

	配件	项目编号
	软管架, 30M 115x70	40195450
	软管架, 60M 150x110	40195451
	软管架, 120M, 200x160	40195452
	软管& 清灰套件支架	40196370
	软管夹, 85	40903030
	软管夹, 56	40903170
	软管管箍 $\Phi 75\text{mm}$	40903180
	软管管箍 112	40903210
	坚固型软管夹, 104-112 ABA	40903270
	终端套管 PE d32	43819001
	终端套管 PE d38	43819011