

Sugeslange PE



Sugeslange PE

- ✓ Temp. område: -40 til +60 °C.
- ✓ Max. vakuum: 50 kPa.

Anvendelsesområder: Enkelt sugeslange, hovedsageligt beregnet til enkel rengøring. Slangen er ikke ledende.

Sugeslange PE

Standarder	Udviklet til at opfylde ISO 21904
------------	-----------------------------------

Modeller

	Art. Nr.	Max vakuum (kPa)	Diameter (mm)	Længde (m)
	40160712	50	25	10
	40160722	50	32	10
	40160731	50	38	5
	40160733	50	38	10
	40160735	50	38	20
	40160741	50	51	5
	40375953	50	32	5
	40160370		38	5
	40160380		50	5
	40160743	50	51	10
	40160745	50	51	20
	43812300			
	43812400			

Modeller

	Art. Nr.	Max vakuum (kPa)	Diameter (mm)	Længde (m)
	43812500			

Tilbehør

	Tilbehør	Art. Nr.
	Slangeophæng 30 mtr. 115 x 70	40195450
	Slangeophæng 60M 150x110	40195451
	Slangeophæng 120M 200x160	40195452
	Slange og tilbehørshylde	40196370
	Slangebånd 85	40903030
	Slangebånd 56	40903170
	Slangebånd 75	40903180
	Slangebånd 112	40903210
	Slangebånd 104-112 ABA Robust	40903270
	Endemuffe PE ø32	43819001
	Endemuffe ø38, pe	43819011