

Industrial vacuum cleaner 306 A

With a pre-separator container this wet/dry vacuum extractor is designed for extraction, collection and separation of liquids, sand, and other granules.



Industrial vacuum cleaner 306 A


- ✓ Easy to empty with tippable container
- ✓ High mobility and great for handling industrial spillage
- ✓ Liquid recovery - wet and dry extraction

With a pre-separator container this wet/dry vacuum extractor is designed for extraction, collection and separation of liquids, sand, and other granules. The industrial vacuum cleaner 306A is air powered and is suitable for wet and dry extraction. This dry/wet vacuum contains two filtration stages that ensure optimum cleaning efficiency. Suction equipment is strong and durable, suitable for building and construction industry and turning and general industries. The wet/dry vacuum containers can be easily tilted to empty their materials. The float ball prevent the first container from overfilling. The trolley is equipped with large wheels for ease of mobility.

Industrial vacuum cleaner 306 A

Certifications	CE
Installation	Outdoor, Indoor
Application	Liquid, Granulate, Swarf
Dustbin volume (l)	40+ 47
Filter Area (m ²)	0,35
Filter type	[bag]
Number of filter elements	1
Filter material	PTFE on PET
Type of hose	PE/C
Compressed air requirement	1,6 Nm ³ /min
[ItemMaxAirFlow]	342
[ItemNoiselevel]	74.0
[ItemMaxVaccum]	-31
Weight (kg)	69
[ItemHWHoseLength]	7,5
[ItemHWHoseDiameter]	51




Models

	Item no
	42130602

Hose types

Hose type	Specification	Temperature range, °C	Hose fittings in free hose end, distribution hose	Hose fitting on free hose end, inlet hose	Hose connection on reel, distribution hose	Hose connection on reel, inlet hose
PEC	For cleaning applications Max vacuum 50 kPa Conductivity < 10 ⁶ Ohm	-40°C - +60°C				

Accessories

	Accessory	Item no
	Control Sfor NE86-96	43222008
	Control Sfor NE 22-76	43220026
	Control Sfor NE 22-76	43220001



Air Powered ejectors All performance data are based on 7 bar supply pressure