

抽排软管PU7

透明聚氨酯软管, $t = 0.7$.用嵌入钢螺旋强化。



抽排软管PU7

- ✓ 灵活
- ✓ 耐磨性和抗老化性很好。
- ✓ 耐燃料、油、溶剂和油脂性很好。









软管灵活，重量轻。适合作为清洁/吸管、运输研磨材料如木屑、锯末、水泥粉尘、颗粒和化工和石化工业中的天然气。耐磨性和抗老化性很好。耐燃料、油、溶剂和油脂性很好。

抽排软管PU7

标准





Designed for ISO 21904 compliance

模型

	项目编号	[ItemMaxVaccum]	直径 (mm)	[ItemLength]	直径A	端部类型 A	长度
	40375982 ^[1]	25	38	10			
	40375989				82	mm	5000
	40375983				51	mm	5000
	40375984				51	mm	10000
	40375985				63	mm	5000
	40375986				63	mm	10000
	40375987				76	mm	5000
	40375988				76	mm	10000

^[1] Hose PU4 Ø 38 mm Max vacuum kPa at 23 ±2°C (25)

配件

	配件	项目编号
	软管夹, 85	40903030
	软管夹, 56	40903170
	软管管箍 Φ75mm	40903180
	软管管箍 112	40903210
	坚固型软管夹, 104-112 ABA	40903270