

Industrial vacuum cleaner 112A

Removal of grease and high viscosity material



Industrial vacuum cleaner 112A



- ✓ Comes with NE 74 powerhead
- ✓ Wet cleaning
- ✓ Vacuuming capacity
- ✓ Easy handling

A high capacity vacuum unit for suction and transportation of grease and other high viscosity material. The material is collected in a plastic bag for easier discharge. Suction equipment is made for heavy duty work. The container is mounted to the trolley by brackets.

Industrial vacuum cleaner 112A

Certifications	CE
Filter type	[bag]
Number of filter elements	1
Filter material	Polyester-teflon
Compressed air requirement	5,3 Nm ³ /min
Max airflow (m ³ /h)	318
Noise level (dB(A))	75.0
Max vacuum (kPa)	-78

Models




	Item no	Type of hose	Hose length (m)	Hose diameter (mm)
	42111202 ^[1]	PVC	7,5	51
	42111203 ^[1]	PU12	5	38

^[1] With brush and conical nozzle

Hose types

Hose type	Specification	Temperature range, °C	Hose fittings in free hose end, distribution hose	Hose fitting on free hose end, inlet hose	Hose connection on reel, distribution hose	Hose connection on reel, inlet hose
PVC	Max vacuum 84 kPA Inner bending radius 60 mm Reinforced with inbedded steel helix	- 20 deg. C. to + 70 Deg. C.				
PU12	Suitable for abrasive material Transparent polyurethane Reinforced with inbedded steel helix	- 40 deg. C. - + 90 Deg. C.				

Accessories

	Accessory	Item no
	Control Sfor NE86-96	43222008
	Control Sfor NE 22-76	43220026
	Control Sfor NE 22-76	43220001



Air Powered ejectors All performance data are based on 7 bar supply pressure