

# Industrial vacuum cleaner 425A

Industrial vacuum cleaner for removal of industrial waste



## Industrial vacuum cleaner 425A


- ✓ Dry waste suction
- ✓ Silo pre-separator with manual outlet valve
- ✓ Fork lift handling
- ✓ Sturdy trolley system with large wheels for uneven ground
- ✓ automatic filtercleaning

Dual container system, designed for removal of industrial waste. This powerful suction unit comes equipped with a silo and filter container fitted with our exclusive nederman vyon self-cleaning filter ensuring the efficient filtration of large quantities of dust. The filter is cleaned automatically when the air supply is turned off. Special swivelling, locking wheels are sized to increase mobility, and make the handling of heavy loads especially simple. The unit is equipped with an adjustable counterweight valve and sack holder for discharge into sacks. The model include slots for handling by forklift.

## Industrial vacuum cleaner 425A

Certifications	CE
Filter type	[cartridge]
Number of filter elements	1
Type of hose	PVC
Compressed air requirement	3,0 Nm <sup>3</sup> /min
[ItemMaxAirFlow]	342
[ItemNoiselevel]	75,5
[ItemMaxVaccum]	-52
Weight (kg)	119
[ItemHVMHoseLength]	7,5
[ItemHVMHoseDiameter]	51




## Models

	Item no
	42142500

## Hose types

Hose type	Specification	Temperature range, °C	Hose fittings in free hose end, distribution hose	Hose fitting on free hose end, inlet hose	Hose connection on reel, distribution hose	Hose connection on reel, inlet hose
PVC	Max vacuum 84 kPA Inner bending radius 60 mm Reinforced with inbedded steel helix	- 20 deg. C. to + 70 Deg.C.				

## Accessories

	Accessory	Item no
	Control Sfor NE86-96	43222008
	Control Sfor NE 22-76	43220026
	Control Sfor NE 22-76	43220001



Air Powered ejectors All performance data are based on 7 bar supply pressure