

425A

Industrial vacuum cleaner for removal of industrial waste



425A


- ✓ Dry waste suction
- ✓ Silo pre-separator with manual outlet valve
- ✓ Fork lift handling
- ✓ Sturdy trolley system with large wheels for uneven ground
- ✓ automatic filtercleaning

Dual container system, designed for removal of industrial waste. This powerful suction unit comes equipped with a silo and filter container fitted with our exclusive nederman vyon self-cleaning filter ensuring the efficient filtration of large quantities of dust. The filter is cleaned automatically when the air supply is turned off. Special swivelling, locking wheels are sized to increase mobility, and make the handling of heavy loads especially simple. The unit is equipped with an adjustable counterweight valve and sack holder for discharge into sacks. The model include slots for handling by forklift.

425A

Certifications	CE
Type de filtre	Filtre à cartouche
Nombre d'éléments filtrants	1
Type de tuyau	PVC
[ItemCompressedAirRequirement]	3,0 Nm ³ /min
[ItemMaxAirFlow]	342
Volume sonore (dB(A))	75,5
[ItemMaxVaccum]	-52
Poids (kg)	119
[ItemHVBHoseLength]	7,5
[ItemHVBHoseDiameter]	51




Modèles

	Référence
	42142500

Types de tuyaux

Type de tuyau	Caractéristiques du tuyau	Température	[HoseFittingDistribution]	Raccords en bout de tuyau de connexion	Type de connexion sur l'enrouleur, tuyau de distribution	[HoseConnectionInlet]
PVC	Vide max. 84 kPa. Rayon de courbure intérieur 60 mm. Renforcé avec spirale en acier.	- 20 deg. C. to + 70 Deg. C.				

Accessories

	Accessoire	Référence
	Commande Sfor NE 86, ss boîtier de commande	4322008
	Commande Sfor NE 22-76, sans boîtier de commande	43220026
	Commande S pour NE 22-76	43220001



Air Powered ejectors All performance data are based on 7 bar supply pressure