Product leaflet

Industrial vacuum cleaner 410E

Industrial vacuum cleaner for removal of industrial waste materials

This content is protected under copyright law, furnished for informational use only, and subject to change without notice. © Nederman Holding AB

Industrial vacuum cleaner 410E

- Dry waste suction
- Silo pre-separator with manual outlet valve
- Fork lift handling
- Sturdy trolley system with large wheels for uneven ground

Dual container system, designed for removal of industrial waste. This powerful suction unit comes equipped with a silo and filter container for the removal of industrial waste materials. Special swivelling, locking wheels are sized to increase mobility, and make the handling of heavy loads simple. The silo is designed to allow the collected material to be discharged over gratings or chutes for the central collection of materials. The model include slots for handling by forklift.

This content is protected under copyright law, furnished for informational use only, and subject to change without notice. © Nederman Holding AB

Industrial vacuum cleaner 410E

Certifications	CE
Installation	Indoor
Filter cleaning method	Mechanical
Application	Dust, Fumes, Swarf, Granulate
Power voltage (V)	230
Frequency (Hz)	50
No of phases	1
Filter type	Cartridge
Number of filter elements	1
Filter material	paper
Electric plug	Euro (CEE 7/2 P+E)
Type of hose	PE/C
Max airflow (m^3/h)	460
Noise level (dB(A))	75
Max vacuum (kPa)	-21,5
Hose length (m)	7,5
Hose diameter (mm)	51
Power (kW)	2,4
Note	With cleaning set, scraping tool and conical nozzle

This content is protected under copyright law, furnished for informational use only, and subject to change without notice. © Nederman Holding AB

Models

	Item no
	42441000[1]

[1] With cleaning set, scraping tool and conical nozzle

Hose types

Hose type	Specification	Temperature range, °C	Hose fittings in free hose end, distribution hose	Hose fitting on free hose end, inlet hose	Hose connection on reel, distribution hose	Hose connection on reel, inlet hose
PEC	For cleaning applications Max vacuum 50 kPa Conductivity < 10^6 Ohm	-40°C - +60°C				

This content is protected under copyright law, furnished for informational use only, and subject to change without notice. © Nederman Holding AB