Produktový list

410E

Industrial vacuum cleaner for removal of industrial waste materials

This content is protected under copyright law, furnished for informational use only, and subject to change without notice. © Nederman Holding AB

410E

- Dry waste suction
- Silo pre-separator with manual outlet valve
- Fork lift handling
- Sturdy trolley system with large wheels for uneven ground

Dual container system, designed for removal of industrial waste. This powerful suction unit comes equipped with a silo and filter container for the removal of industrial waste materials. Special swivelling, locking wheels are sized to increase mobility, and make the handling of heavy loads simple. The silo is designed to allow the collected material to be discharged over gratings or chutes for the central collection of materials. The model include slots for handling by forklift.

This content is protected under copyright law, furnished for informational use only, and subject to change without notice. © Nederman Holding AB

410E

Certifikace	CE
Instalace	Vnitřní
Metoda čištění filtru	Mechanický
Použití	Prach, Dýmy, Třísky, Granulát
Napětí (V)	230
Frekvence (Hz)	50
Počet fází	1
Typ filtru	Vložka
Počet filtračních elementů	1
Materiál filtru	Papír
Elektrická zástrčka	Euro (CEE 7/2 P+E)
Typ hadice	PE/C
[ItemMaxAirFlow]	460
[ItemNoiselevel]	75
[ItemMaxVaccum]	-21,5
[ItemHVHoseLength]	7,5
[ItemHVHoseDiameter]	51
Výkon (kW)	2,4
Ujasnění technických údajů	S čisticí sadou, škrabákem a kuželovou tryskou

This content is protected under copyright law, furnished for informational use only, and subject to change without notice. © Nederman Holding AB

Models

	Item number
	42441000[1]

[1] S čisticí sadou, škrabákem a kuželovou tryskou

Typ hadice

Typ hadice	Specifikace	Rozsah teplot, °C	Hadicový fitink na volném konci hadice, distribuční hadice	Hadicový fitink na volném konci hadice, přívodní hadice	Připojení hadice na naviják, distribuční hadice	Připojení hadice na naviják, přívodní hadice
PEC	Pro čistící aplikace Max podtlak 50kPa Vodivost 10^3 to 10^6 Ohm/m	-40°C - +60°C				

This content is protected under copyright law, furnished for informational use only, and subject to change without notice. © Nederman Holding AB