Product leaflet

Cable Reel 744

Durable low voltage cable reel for signal transmission. 48V AC/DC 2ADurable low voltage cable reel for signal transmission. 48V AC/DC 2A.

This content is protected under copyright law, furnished for informational use only, and subject to change without notice. © Nederman Holding AB

Cable Reel 744

- Rubber cable
- IP44 protected
- High impact resistant material
- Durable
- Easy to use

Durable cable reel for professional usage in light industrial applications when signal transmission is needed. The reel is produced in high impact resistant material and has an IP44 classification, which means it is protected from water splashes. Perfect for signal transmission in applications like overfill protection on tankers, crane trucks, camera surveillance and more. The long rubber cable (50 m, 164 ft) make the reel easy to use.

This content is protected under copyright law, furnished for informational use only, and subject to change without notice. © Nederman Holding AB

Cable Reel 744

Certifications	[ce]
Protection class	IP44
Power voltage (V)	48
No of phases	1
Electric plug	[without]
Amperage (A)	2
Conductors (No. x mm²)	2Gx1
Media	[power]
Colour	Black
Distribution cable length (m)	50
Connection cable, Length (m)	1
Connection cable (No. x mm²)	2 x 1
Corrosion resistance	Standard
Electric/Spring driven	Spring

This content is protected under copyright law, furnished for informational use only, and subject to change without notice. © Nederman Holding AB

Models

	Item no
	30700244

This content is protected under copyright law, furnished for informational use only, and subject to change without notice. © Nederman Holding AB