Product leaflet

Enrollador de cable 744

Durable low voltage cable reel for signal transmission. 48V AC/DC 2A



This content is protected under copyright law, furnished for informational use only, and subject to change without notice. © Nederman Holding AB

Enrollador de cable 744

- Rubber cable
- IP44 protected
- High impact resistant material
- Durable
- Easy to use

Durable cable reel for professional usage in light industrial applications when signal transmission is needed. The reel is produced in high impact resistant material and has an IP44 classification, which means it is protected from water splashes. Perfect for signal transmission in applications like overfill protection on tankers, crane trucks, camera surveillance and more. The long rubber cable (50 m, 164 ft) make the reel easy to use.

This content is protected under copyright law, furnished for informational use only, and subject to change without notice. © Nederman Holding AB

Enrollador de cable 744

Certificaciones	CE
Case de protección	IP44
Voltaje (V)	48
Fases	1
Enchufe eléctrico	sin
Amperaje (A)	2
Conductores (No. x mm²)	2Gx1
Fluidos	Potencia
Color	negro
Longitud del cable de distribución (m)	50
Cable de conexión, longitud (m)	1
Cable de conexión (No. x mm²)	2 x 1
[ItemCorrosionResistance]	Estándar
[ItemElectricSpringDriven]	Muelle

This content is protected under copyright law, furnished for informational use only, and subject to change without notice. © Nederman Holding AB

Models

	Item number
	30700244

This content is protected under copyright law, furnished for informational use only, and subject to change without notice. © Nederman Holding AB