

NRS rotary valves, type 4,10,20,30 and 10-Q

Continuous emptying of the dust collector hopper



NRS rotary valves, type 4,10,20,30 and 10-Q

- ✓ The NRS type rotary valve is used to transfer material between two separate systems. In pneumatic conveying systems discharge is usually required from the filter or cyclone to the silo, at atmospheric pressure. This is an ideal application for the NRS type rotary valve. The rotary valve can be used for most material types, though the particle size must not exceed 13 x 13 x 13 mm (.5 x .5 x .5 in). The NRS type rotary valve is modular and robustly constructed in heavy steel plate. The rotor of each module is equipped with an elastic clutch. This reduces the possibility of damage in use and maximises the life of the unit. The rotor has special rubber seals, which provide an effective air lock between the inlet and the outlet. This type of rotary valve is also available in an ATEX certified version for explosive dusts type St1 and St2. The NRSZ is a protective system according to ATEX definition.
- ✓ Long lifetime. The rotor is equipped with an elastic clutch, which reduces the possibility of damage in use and maximizes the life of the unit.
- ✓ Effective air lock between the inlet and outlet provided due to the special rubber blends.

The NRS type rotary valve is used to transfer material between two separate systems. In pneumatic conveying systems discharge is usually required from the filter or cyclone to the silo, at atmospheric pressure. This is an ideal application for the NRS type rotary valve.

The rotary valve can be used for most material types, though the particle size must not exceed 13 x 13 x 13 mm (.5 x .5 x .5 in).

The NRS type rotary valve is modular and robustly constructed in heavy steel plate. The rotor of each module is equipped with an elastic clutch. This reduces the possibility of damage in use and maximises the life of the unit. The rotor has special rubber seals, which provide an effective air lock between the inlet and the outlet.

NRS rotary valves, type 4,10,20,30 and 10-Q

Certifications	CE
Protection class	IP55
Installation	Outdoor, Indoor
Suitable for combustible dust	False
Application	Dust

Models

	Item no	Weight (kg)	Power (kW)
	73009015 ^[1]	50	
	73009016 ^[2]	67	0,18
	73009018 ^[3]	67	0,75
	73009019 ^[4]	107	
	73009021 ^[4]	124	0,75
	73009022 ^[5]	214	
	73009024 ^[6]	243	0,75
	73009025 ^[7]	321	
	73009027 ^[8]	338	0,75

^[1] Capacity at 100% filling - 2 m³/h per RPM. This product is not included in our free of charge carriage offer. For a carriage cost please contact Nederman UK.

^[2] Capacity at 100% filling - 14 m³/h. This product is not included in our free of charge carriage offer. For a carriage cost please contact Nederman UK.

^[3] Capacity at 100% filling - 65 m³/h. This product is not included in our free of charge carriage offer. For a carriage cost please contact Nederman UK.

^[4] Without motor. Capacity at 100% filling - 4,9 m³/h per RPM. This product is not included in our free of charge carriage offer. For a carriage cost please contact Nederman UK.

^[5] Without motor. Capacity at 100% filling 9,8 m³/h per RPM. This product is not included in our free of charge carriage offer. For a carriage cost please contact Nederman UK.

^[6] Capacity at 100% filling - 314 m³/h. This product is not included in our free of charge carriage offer. For a carriage cost please contact Nederman UK.

^[7] Without motor. Capacity at 100% filling - 14,7 m³/h per RPM. This product is not included in our free of charge carriage offer. For a carriage cost please contact Nederman UK.

^[8] Capacity at 100% filling - 471 m³/h. This product is not included in our free of charge carriage offer. For a carriage cost please contact Nederman UK.

Accessories

	Accessory	Item no
	Rotation sensor for NRS with assembly kit	73008689
	Tool for setting the rotor in NRSZ4/10	73008777







