Product leaflet

OMF 2x4000 SM

FibreDrain® olietågefilter (emulsion) for kontinuerlig drift.

This content is protected under copyright law, furnished for informational use only, and subject to change without notice. © Nederman Holding AB

OMF 2x4000 SM

- Tre filter trin, forudskiller som option
- Målere til registrering af trykfald over hvert filter trin
- Drain: 4 off 1 1/2"
- Non-vibration fan suspension system

Nederman OMF olietåge eliminiator er designet til hat håndtere store mængder af emulsionståge under kontinuerlig drift. De er udviklet med fokus på høj effektivitet og lave vedligeholdelsesomkostninger.

Nederman OMF 2x4000 har som standard tre filter trin, hvor de første to trin består af filterkassetter med Nederman FibreDrain® teknologi. Nederman har flere forskellige typer af filter til forskellige typer af applikationer. Det tredje trin består af et HEPA filter i i filterklasse H13 med en effektivitet på 99,95% for MPPS iht. EN1822. Alle Nederman OMF enheder er forberedt for brug af forfilter.

This content is protected under copyright law, furnished for informational use only, and subject to change without notice. © Nederman Holding AB

OMF 2x4000 SM

Cerifikat	CE
Standarder	2009/125/EC
Volumen (for fragt m³)	10,6
Beskyttelsesklasse	IP55
Filter udskilningsgrad (%)	99,95
Installation	Indendørs
Materiale	Metalplade, malet både ind- og udvendigt
Metode for filterrensning	[Draining]
Arbejdstryk (kPa)	Max 4500 Pa
Kapacitet (max luftvolumen m3/h)	8000
Driftstemperatur	60°C (begrænset af filter)
Spænding (V)	400/690
Frekvens (Hz)	50
Faser	3
Antal filter	12
Strøm (A)	19,5 / 11,3
Farve	NCS-S 1005 B20G
Vægt (kg)	1140
Effekt (kW)	11
Afklaring af tekniske data	Plus fire filter element som option.

This content is protected under copyright law, furnished for informational use only, and subject to change without notice. © Nederman Holding AB

Modeller

	Art. Nr.
	12401151[1]
	12401152[1]

[1] Plus fire filter element som option.

This content is protected under copyright law, furnished for informational use only, and subject to change without notice. © Nederman Holding AB

Tilbehør

	Tilbehør	Art. Nr.
	Drænpumpeboks, 50 Hz	12400054
	Opsamlingsbeholder med rør	12400764
	Forfilter ORF 610x610x96 G4I	12400039
	FibreDrain Filter F66 OMF 1	12400009
	FibreDrain Filter F66 OMF 2	12400010
	Hepa DCM H13 610x610x292	12400012
	Inlet adapter OSF 4x2000, OMF 2x4000	12401161
	Extension structure OSF 2x2000, OMF 2x4000	12401164
	Fan enclosure 2 filters in depth	12401109
	OMF/OSF Lyddæmper 90/Ø500	12400038
	FibreDrain Pumpbox KTF82-200 / 50Hz	12401330
	OSF/OMF Instruction manual for mounting system for electric components	12401342
	OMF/OSF/MQL mounting system for electrical components	12401341

This content is protected under copyright law, furnished for informational use only, and subject to change without notice. © Nederman Holding AB

Tilbehør

	Tilbehør	Art. Nr.
	Frekvensomformer med 5kPa tryktransmitter. 11 kW indbygget i IP66 skab	73008918
	Frekvensomformer med 5kPa tryktransmitter. 15 kW indbygget i IP66 skab	73008919

This content is protected under copyright law, furnished for informational use only, and subject to change without notice. © Nederman Holding AB

This content is protected under copyright law, furnished for informational use only, and subject to change without notice. © Nederman Holding AB





This content is protected under copyright law, furnished for informational use only, and subject to change without notice. © Nederman Holding AB





This content is protected under copyright law, furnished for informational use only, and subject to change without notice. © Nederman Holding AB





This content is protected under copyright law, furnished for informational use only, and subject to change without notice. © Nederman Holding AB