

FilterBox 10A NANO

Automatically cleaned for light to medium welding fumes and dust applications, with a unique filtration system designed specific for welding.



FilterBox 10A NANO

- ✓ Using the latest nanofiber technology for filtration
- ✓ Automatically operated filter cleaning with compressed air for long filter life.
- ✓ LCD panel with operating status and menu system for parameter setup and settings. Possibility to connect a welding sensor clamp to automatically start the fan.
- ✓ Automatic damper preventing dust from leaking out while cleaning. Dust free filter replacement and emptying of dust bin.
- ✓ MERV 15 rated filter *ASHRAE Standard 52.2, 2017, third party tested. Approved for welding fumes category W3 according to ISO 21904-1, third party certified.

The FilterBox 10A NANO offers a flexible and easy-to-move solution for your workshop, using the latest nanofiber filter technology for unrivalled efficiency and tool life. Perfect solution for welding of aluminium, steel and stainless steel, also including high alloy applications.

The FilterBox 10A NANO is equipped with a N24 fan for a maximum air flow capacity of 1 000 m³/h (600 CFM). The nanofiber media technology utilized in the extra large 17m² (183 ft²) cartridge is ideal for frequent welding. It offers significant performance advantages like higher efficiency and surface loading properties which results in more effective filter cleaning and longer cleaning intervals. Advantages that will impose benefits in terms of filter life, productivity and lower cost of ownership.

The advanced filter control system with audible alarm, LEDs and LCD screen provides additional safety. And the integrated silencer provides extra comfort, reduces noise from the fan and outlet air. Additional protection from harmful particles is provided if a HEPA filter is installed (optional).

Note! FilterBox is not for use in environments where combustible dust or gases are present, and it is not for use in filtering combustible dust or gases.

FilterBox 10A NANO

Sertifikalar	CE
Koruma sınıfı	IP 54
Filtreleme kalitesi (%)	99,9
Kurulum	[Indoor]
Frekans(Hz)	50
Filtre türü	[cartridge]
Filtre adedi	1
Elektrik prizi	[without]
[ItemMounting]	[mobile]
Ağırlık (kg)	102
[ItemFilterCleaningMethod]	[CompressedAir]
[ItemExtractionMethod]	[extraction arm]
[ItemFilterChangeIndication]	False
[ItemFumeAndDustApplication]	[Light-Medium]

Models

	Item number	Kol uzunluđu (m)	Güç Volt (V)	Faz adedi	Güç (kW)	[ItemMaxAirFlow]
	12694663 ^[1]	3 (Original)	230	3	0,9	
	12695763 ^[1]	Bulunmaz	400	3	0,9	1000
	12694863 ^[1]	3 (Original)	230	1	0,75	
	12694763 ^[1]	3 (Original)	400	3	0,9	

^[1] Filter class F9 (EN779), MERV 15 (ASHRAE 52.2)

Accessories

	Accessory	Item number
	High efficiency Main Replacement filter for FilterBox. Nanofiber 17 m ² (183 ft ²). Compatible with all FilterBoxes with Pneumatic cleaning.	12377251
	FilterBox ePTFE High Efficiency Replacement filter. 13m ² (140 ft ²).	12377252
	Sensor clamp to be attached to the earth cable of the welding power source.	14372199
	HEPA filter H14 10m ² Filterbox	12376756
	LED ışığı/fan anahtarı orijinal	10376922
	Orijinal/NEX MD-gövde için kıvılcım koruması	10551335
	HEPA filter H13 10m ² Filterbox	12376615
	Spot ışığı orijinal, (LED) 24V, 5W	12376616
	Bags for Filterbox dust bin, 10pcs	12376618
	çıkış, Kanal bağlantısı D=200mm	12376749
	İkiz modül mavi	12376801