

FilterBox 12A NANO

Automatically cleaned for medium to heavy welding fumes and dust applications, with a unique filtration system designed specific for welding.



FilterBox 12A NANO

- ✓ Using the latest nanofiber technology for filtration.
- ✓ Automatically operated filter cleaning with compressed air for long filter life.
- ✓ LCD panel with operating status and menu system for parameter setup and settings. Possibility to connect a welding sensor clamp to automatically start the fan.
- ✓ Automatic damper preventing dust from leaking out while cleaning. Dust free filter replacement and emptying of dust bin.
- ✓ MERV 15 rated filter *ASHRAE Standard 52.2, 2017, third party tested. Approved for welding fumes category W3 according to ISO 21904-1, third party certified.

When mobility, flexibility and a compact footprint is key, a mobile solution is often the best way to avoid contaminant exposure. Nederman FilterBox range of mobile dust and fume extraction units are easy to move around your factory to wherever the extraction is needed. The wide product range makes it easy to find a model with the capacity, features and filter type needed.

The FilterBox 12A+ is equipped with a powerful fan for a maximum air flow capacity of 1 200 m³/h (700 CFM). The nanofiber media technology utilized in the extra large 17m² (183 ft²) cartridge is ideal for frequent welding. It offers significant performance advantages like higher efficiency and surface loading properties which results in more effective filter cleaning and longer cleaning intervals. Advantages that will impose benefits in terms of filter life, productivity and lower cost of ownership.

The unit has an advanced filter control system indicating the pressure drop with a series of LED's as well as on the LCD display. When the air flow is too low an audible alarm precedes the automatic, motorized compressed air cleaning sequence. An integrated silencer reduces noise from the fan and outlet air. Additional protection from harmful particles is provided if a HEPA filter is installed (optional).

FilterBox 12A+ is available as a mobile unit on wheels but can be fixed mounted with an accessory kit.

Note! FilterBox is not for use in environments where combustible dust or gases are present, and it is not for use in filtering combustible dust or gases.

FilterBox 12A NANO

Certifications	CE
Standard	ISO 21904
Protection class	IP 54
Installation	Indoor
Application	Fumes
Power Voltage (V)	400
Frequency (Hz)	50
No of phases	3
Filter type	[cartridge]
Number of filter elements	1
Electric plug	without
[ItemMounting]	[mobile]
Weight (kg)	115
Filter cleaning method	Compressed air
Power (kW)	2,2
[ItemExtractionMethod]	extraction arm
[ItemFilterChangeIndication]	False
[ItemFumeAndDustApplication]	Medium-Heavy

Models

	Item no	Arm length (m)	[ItemMaxAirFlow]
	12696063 ^[1]	3 (Original)	1200
	12696863 ^[1]	Without	

^[1] Filter class F9 (EN779), MERV 15 (ASHRAE 52.2)

Accessories

	Accessory	Item no
	FilterBox ePTFE High Efficiency Replacement filter. 13m ² (140 ft ²).	12377252
	High efficiency Main Replacement filter for FilterBox. Nanofiber 17 m ² (183 ft ²). Compatible with all FilterBoxes with Pneumatic cleaning.	12377251
	Sensor clamp	14372199
	Filter-PW-FB-13	12332672
	HEPA filter H14 10m ² Filterbox	12376756
	Bags for Filterbox dust bin, 10pcs	12376618
	HEPA filter H13 10m ² Filterbox	12376615
	LED light/fan switch for Original hood. Including: LED 24V, cable, switch, socket, lens, screws, nuts, cable straps, spring	10376922
	Spotlight original, (LED) 24V, 5W	12376616
	Outlet with duct connection D=200mm	12376749