

FlexPAK

Frequency controlled compact high vacuum dust collector unit to be used for many different applications. Typically 2-10 users.



FlexPAK

- ✓ Easy to install
- ✓ Built in PLC functions
- ✓ Low operating cost
- ✓ Reliable
- ✓ Suitable for a wide range of applications

The FlexPAK is a frequency controlled high vacuum dust collector unit. The unit is designed for the extraction of welding fume, grinding dust, metal chips etc. FlexPAK is suitable for cleaning the workplace, the shop floor and machines. It is also very suitable for on-tool and on-torch applications. FlexPAK regulates the speed of the motor automatically depending on the vacuum demand. Compared to traditional controllers, FlexPAK provides an optimal, and well-balanced vacuum according to the need, ensuring energy-saving operation. The FlexPAK have different running modes to meet specific customer needs. The FlexPAK can easily switch between generating as much vacuum as possible, typically for applications with long piping or material transportation, or maintaining a constant vacuum level, typically useful for welding fume or grinding dust applications.

FlexPAK

Sertifikalar	CE
Koruma sınıfı	IP 42
Kurulum	[Indoor], [Outdoor]
Patlayıcı toz için ideal	False
Filtre temizlik metodu	[ReverseAirPulse]
[ProductApplication]	[granulate], [grit], [fumes], [swarf], [dust]
Güç Volt (V)	400
Frekans(Hz)	50/60
Faz adedi	3
Filtre türü	[bag]
Filtre adedi	1
[ItemCompressedAirRequirement]	6-7 bar
[ItemMaxVacuum]	35
Ağırlık (kg)	439
Güç (kW)	18,5

Models

	Item number
	40050361
	40050366
	40050367

Accessories

	Accessory	Item number
	Replacement plastic Bag 730x900, 20pcs, in dissipative material for EX applications	40118800
	Izgara spiro 160mm	40130230
	Overheat indication via a melting fuse providing safety alerts if the unit overheats while not running but still having power. If placed in EX zone, intrinsic safe circuit is required.	40116540
	sıkıştırılmış hava anahtarı, 3 bar	40620370
	Anahtar bağlantı kesici MS3-KG64	40122290
	Diferansiyel basınç anahtarı 3-15 kPa NC	40375273
	Seviye göstergesi BLI 10-40VDC komple	40780710
	Susturucu LT160	40139090
	flaşlı boru Ø 150, 1 m	40375263
	flaşlı Dirsek 90° Ø 150	40375264
	flaşlı boru d150, 0,5m	40376525
	flaşlı Dirsek 45° Ø 150	40376770
	Dezeminektör 220x540	40376771

