

Product leaflet

112A

Removal of grease and high viscosity material



112A



- ✓ Comes with NE 74 powerhead
- ✓ Wet cleaning
- ✓ Vacuuming capacity
- ✓ Easy handling

A high capacity vacuum unit for suction and transportation of grease and other high viscosity material. The material is collected in a plastic bag for easier discharge. Suction equipment is made for heavy duty work. The container is mounted to the trolley by brackets.

112A

Certificeringen	CE
Filtertype	Zakken filter
Aantal filterelementen	1
Persluchtsbehoefte	5,3 Nm ³ /min
[ItemMaxAirFlow]	318
[ItemNoiselevel]	75.0
Max. vacuüm	-78

Models



	Item number	Slangtype	[ItemHVVHoseLength]	[ItemHVVHoseDiameter]
	42111202 ^[1]	PVC	7,5	51
	42111203 ^[1]	PU12	5	38

^[1] With brush and conical nozzle

Hose types

Slang type	Specificaties	Temperatuurbereik, °C	Slangkoppelingen einde werkslang	Slangkoppelingen einde koppelslang	Slangaansluiting op de haspel, werkslang	Slangaansluiting op de haspel, koppelslang
PVC	Max vacuüm 84 kPA Binnenbuigstraal 60 mm Verstevigd met verzonken stalen spiraal	- 20 deg. C. to + 70 Deg. C.				
PU12	Geschikt voor abrasief materiaal Transparant polyurethaan Verstevigd met verzonken stalen spiraal	- 40 deg. C. - + 90 Deg. C.				

Accessories

	Accessory	Item number
	Control S for NE86-96, wo/control box	43222008
	Control S for NE 22-76, wo/control box	43220026
	Control S for NE 22-76	43220001



Air Powered ejectors All performance data are based on 7 bar supply pressure