

Product leaflet

QF duct, Stainless

Stainless QF ducting



QF duct, Stainless

- ✓ QF for fast installation with no special tools, no painting, flexible working
- ✓ Easy to assemble installation components
- ✓ Neat slip duct connections to adapt and adjust ducting on site during installation
- ✓ Laser welded straight ducts for smoother surface and enhanced leak resistance
- ✓ Easy to extend or take apart completely for cleaning, reconfiguring or relocation

Manufactured from galvanised steel or stainless steel with laser welded seams, which have smoother internal surfaces and provide greatly enhanced leak resistance, QF ducting offers an unbeatable solution for all general purpose dust extraction duties.













The Quick-Fit™ clip features a generously dimensioned sealing gasket held firmly in place by positive overcentre clamping action over the rolled collars at the duct ends to be joined. For added security, a locking pin may be inserted.

QF duct, Stainless







[ProductOperatingTemperatureRange]

-20° C - 200° C

Models

	Item number	Diameter A	End Type A	Length
	8240020721	80	QF	2000
	8240020724	100	QF	2000
	8240020727	125	QF	2000
	8240020730	140	QF	2000
	8240020733	150	QF	2000
	8240020736	160	QF	2000
	8240020739	180	QF	2000
	8240020742	200	QF	2000
	8240020745	224	QF	2000
	8240020748	250	QF	2000
	8240020751	300	QF	2000
	8240020754	315	QF	2000
	8240020757	350	QF	2000

Models

	Item number	Diameter A	End Type A	Length
	8240020760	400	QF	2000
	8240020763	450	QF	2000
	8240020766	500	QF	2000
	8240020769	560	QF	2000
	8240020772	630	QF	2000
	8240020775	710	QF	2000