

Product leaflet

425A

Industrial vacuum cleaner for removal of industrial waste



425A


- ✓ Dry waste suction
- ✓ Silo pre-separator with manual outlet valve
- ✓ Fork lift handling
- ✓ Sturdy trolley system with large wheels for uneven ground
- ✓ automatic filtercleaning

Dual container system, designed for removal of industrial waste. This powerful suction unit comes equipped with a silo and filter container fitted with our exclusive nederman vyon self-cleaning filter ensuring the efficient filtration of large quantities of dust. The filter is cleaned automatically when the air supply is turned off. Special swivelling, locking wheels are sized to increase mobility, and make the handling of heavy loads especially simple. The unit is equipped with an adjustable counterweight valve and sack holder for discharge into sacks. The model include slots for handling by forklift.

425A

Certificeringen	CE
Filtertype	Cartridge filter
Aantal filterelementen	1
Slangtype	PVC
Persluchtsbehoefte	3,0 Nm ³ /min
[ItemMaxAirFlow]	342
[ItemNoiselevel]	75,5
Max. vacuüm	-52
Gewicht (kg)	119
[ItemHVBHoseLength]	7,5
[ItemHVBHoseDiameter]	51




Models

	Item number
	42142500

Hose types

Slang type	Specificaties	Temperatuurbereik, °C	Slangkoppelingen einde werkslang	Slangkoppelingen einde koppelslang	Slangaansluiting op de haspel, werkslang	Slangaansluiting op de haspel, koppelslang
PVC	Max vacuüm 84 kPA Binnenbuigstraal 60 mm Verstevigd met verzonken stalen spiraal	- 20 deg. C. to + 70 Deg. C.				

Accessories

	Accessory	Item number
	Control S for NE86-96, wo/control box	43222008
	Control S for NE 22-76, wo/control box	43220026
	Control S for NE 22-76	43220001



Air Powered ejectors All performance data are based on 7 bar supply pressure