

# Fume Eliminator 860

Portable source capture for on-torch extraction



## Fume Eliminator 860

- ✓ Portable and easy to carry.
- ✓ Automatically maintains the set extraction flow - ideal for on-torch applications
- ✓ Warnings at malfunction and when the filter is 85% and 100% full
- ✓ High efficiency Nanofiber filter protecting the user from submicron particles. F9 (EN 779) MERV 14 (ASHRAE 52.2)
- ✓ Designed for torches requiring max 18 kPa at connection point - according to ISO 21904


The Fume Eliminator 860 is designed to be carried to the working area. Although it can be used with a nozzle, it is specifically developed for on-torch applications - connected directly to the welding torch, it extracts the fume directly at the source. The FE 860 has a knob to set the desired suction level, an automatic start/stop function, which starts the unit as soon as the welding begins and significantly improved motor performance (versus the FE840/841).

The FE 860 is suitable for extraction of fume in maintenance welding applications and is compliant with ISO 21904 (W3).

# Fume Eliminator 860

证书	CE
标准	ISO 21904-1
过滤效能 (%)	99.7
安装	室内
应用	烟气
电压 (V)	230
频率 (Hz)	50
电源相数	1
除尘器类型	滤筒式过滤器
滤芯数量	1
插头类型	欧式 (CEE 7/2 P+E)
[ItemWorkingPressure]	25
重量 (公斤)	16
清洁方式	一次性滤芯
[ItemHVHoseDiameter]	50
功率 (kW)	1,3
[ItemExtractionMethod]	手工焊接
[ItemFilterChangeIndication]	False

## 模型

	项目编号
	70842010

## 配件

	配件	项目编号
	金属过滤器, 用于FE 840/841	70282004
	金属过滤器, 用于FE 840/841	70284001
	Filter nano disposable	70377313
	Superflex Hose crushproof Ø50 5m	70377340
	超柔软抗压软管, 直径50毫米, 长度2.5米	70377336
	超柔软抗压软管, 直径50毫米, 长度15米	70377339
	烟道吸嘴, TM-80	70851000
	法兰吸嘴, PM-300	70853000
	漏斗型吸嘴, TM-200	70854000
	Hose connection M50 Ø50	70377337