

Producto leaflet

# Fume Eliminator 860

Captura portátil para la extracción en la antorcha



## Fume Eliminator 860

- ✓ Portátil y fácil de transportar
- ✓ Mantiene automáticamente el caudal de extracción ajustado: ideal para aplicaciones en la antorcha.
- ✓ Avisos en caso de avería y cuando el filtro está lleno al 85% y al 100%.
- ✓ Filtro de nanofibras de alta eficacia que protege al usuario de partículas submicrónicas. F9 (EN 779) MERV 14 (ASHRAE 52.2)
- ✓ Diseñado para antorchas que requieren un máximo de 18 kPa en el punto de conexión - según ISO 21904


El Fume Eliminator 860 está diseñado para ser transportado a la zona de trabajo. Aunque puede utilizarse con una boquilla, se ha desarrollado específicamente para aplicaciones en la antorcha: conectado directamente a la antorcha de soldadura, extrae los humos directamente en la fuente. El FE 860 tiene un mando para ajustar el nivel de aspiración deseado, una función automática de arranque/paro, que pone en marcha la unidad en cuanto comienza la soldadura, y un rendimiento del motor significativamente mejorado (en comparación con el FE840/841).

El FE 860 es adecuado para la aspiración de humos en aplicaciones de soldadura de mantenimiento y cumple la norma ISO 21904 (W3).











# Fume Eliminator 860

[ProductCertifications]	[ce]
[ProductStandards]	ISO 21904-1
[ProductFilterefficiency]	99.7
[ProductInstallation]	Interior
[ProductApplication]	Humos
[ProductWorkingpressure]	25
[ProductMaxAirFlow]	180
[ProductHoseLength]	2.5
[ProductFilterArea]	5.3
[ItemPowerVoltage]	120
[ItemFrequency]	60
[ItemNoofphases]	1
[ItemFilterType]	Cartucho
[ItemNbrofFilterElements]	1
[ItemFilterMaterial]	Celulosa con nanofibra
[ItemElectricplug]	[us]
[ItemWeight]	16
[ItemFilterCleaningMethod]	[OneWayFilter]
[ItemHVVHoseDiameter]	50
[ItemPower]	1,25
[ItemExtractionMethod]	[on-torch]
[ItemFilterChangeIndication]	False

## Modelos

	No. De Artículo
	70842040

## Accesorios

	Accesorio	No. De Artículo
	Metal filter for FE 840/841/860	70282004
	Metal filter compl. for FE 840/841/860	70284001
	Filter nano disposable	70377313
	Superflex Hose crushproof Ø50 5m	70377340
	Superflex Hose crushproof Ø50 2,5m Black PVC-CP with Embedded Spring Steel Coil - Flame Retardant Outer Layer. No connectors included.	70377336
	Superflex Hose crushproof Ø50 15m	70377339
	Funnel nozzle TM-80	70851000
	Flange nozzle PM-300	70853000
	Funnel nozzle TM-200	70854000
	Hose connection M50 Ø50	70377337