

# TECHNICAL DATA SHEET: SILENCER RLDQ/RLBQ

RLDQ Silencer		
Ø mm	D mm	L m
100	300	
120*	320	
125	325	
140	340	
150	350	
160	360	
180	380	
200	400	Available in three length options: 0,5 m 1 m 2 m
224	424	
250	450	
300	500	
315	515	
350	550	
400	600	
450	650	
500	700	
560	760	
630	830	
710	910	

RLBQ Silencer with Baffle		
Ø mm	D mm	L m
300	500	Available in three length options: 0,5 m 1 m 2 m
315	515	
350	550	
400	600	
450	650	
500	700	
560	760	
630	830	
710	910	



RLDQ



RLBQ

### Additional Notes

At temperatures ranging between 200° C and 250° C, the zinc-iron alloy layers in galvanised steel will continue to provide a high level of protection from corrosion. However, there may be some peeling, changes in mechanical properties, and reduction in the corrosion protection. Recommended max. service temperature is +80° C.

\* Ø120 is only available in FB system.

### Compliance / Rating of Product Components

Product	Material	Compliance / Rating
Silencer	Galvanised	DX51D with Z275 Coating
Joka Seal Metal Sealant 2315	Aceton Blend	AAMA Specification 801.1

### Temperature Rating of Product Components

	Silencer	Sealant
200°C	Galvanised Steel	Joka Seal Metal Sealant 2315
121°C		
-20°C		

