

# TECHNICAL DATA SHEET: QUICK-FIT (QF) WEATHER COWL

Ø mm	B mm	C mm	Galvanised Steel Thickness mm	Weight kg
125	250	150	0,9	1,5
140	350	190	0,9	1,9
150	350	190	0,9	2,0
160	350	190	0,9	2,1
180	400	220	0,9	2,5
200	400	220	0,9	2,6
225	500	240	0,9	2,6
250	500	240	0,9	3,0
300	650	340	0,9	5,2
315	650	340	0,9	5,3
350	650	340	0,9	5,9
400	750	370	0,9	8,1
450	750	370	0,9	8,2
500	950	440	0,9	9,9
550	950	440	0,9	10,5
600	1050	480	0,9	13,9
630	1050	480	0,9	14,0
650	1050	480	0,9	14,1
700	1200	570	0,9	21,4
750	1200	570	0,9	21,7
800	1400	610	1,25	25,6
850	1400	610	1,25	25,8
900	1550	680	1,25	29,5
950	1550	680	1,25	29,8
1000	1700	720	1,25	35,9



Temperature Rating of Product Components		
	Weather Cowl	Sealant
200°C	Galvanised Steel	Joka Seal Metal Sealant 2315
121°C		
-20°C		

Compliance / Rating of Product Components		
Product	Material	Compliance / Rating
Weather Cowl	Galvanised	DX51D with Z275 Coating
Joka Seal Metal Sealant 2315	Aceton Blend	AAMA Specification 801.1

**Additional Notes**

At temperatures ranging between 200° C and 250° C, the zinc-iron alloy layers in galvanised steel will continue to provide a high level of protection from corrosion. However, there may be some peeling, changes in mechanical properties, and reduction in the corrosion protection. Recommended max. service temperature is +80°C.

Also supplied in flanged design.

