

# TECHNICAL DATA SHEET:

## HIGH VACUUM REINFORCED BENDS, 90° & 45°

### Reinforced Steel Bend with swarf box, 90°


| Ø<br>mm | X<br>mm | Y<br>mm | Mild Steel<br>Thickness<br>mm | Weight<br>kg |
|---------|---------|---------|-------------------------------|--------------|
| 063     | 265     | 115     | 1,5                           | 1,5          |
| 102     | 400     | 185     | 2,0                           | 4,9          |



High Vacuum Reinforced Bend, 90°

### Reinforced Steel Bend with swarf box, 45°

| Ø<br>mm | X<br>mm | Y<br>mm | Mild Steel<br>Thickness<br>mm | Weight<br>kg |
|---------|---------|---------|-------------------------------|--------------|
| 063     | 185     | 35      | 1,5                           | 1,0          |
| 102     | 260     | 45      | 2,0                           | 3,8          |



High Vacuum Reinforced Bend, 45°

### Additional Notes

Recommended max. service temperature is +80° C.

Paint is RAL5009 Blue.

### Compliance / Rating of Product Components

| Product         | Material   | Compliance / Rating |
|-----------------|------------|---------------------|
| Reinforced Bend | Mild Steel | S235JR/EN           |

### Temperature Rating of Product Components

|       | Reinforced Bend |
|-------|-----------------|
| 200°C | Mild Steel      |
| -20°C |                 |