

TECHNICAL DATA SHEET:

RMAD & RMAE MILD STEEL SMOOTH ADAPTER

Ø mm	L mm	RMAD Weight kg	RMAE Weight kg
80		0,20	
100		0,25	
120		0,30	
125		0,31	
140		0,35	
150	45	0,37	0,56
160	45	0,39	0,59
180	45	0,44	0,66
200	45	0,49	0,75
225	45	0,55	0,83
250	45	0,62	0,93
300	45	0,74	1,11
315	45	0,78	1,17
350	45	0,86	1,32
400	45	0,99	1,49
450	45	1,11	1,67
500	50	1,23	1,85
550	50	1,36	2,04
600	50	1,48	2,23
630		1,55	

RMAD = 2 mm steel thickness.
RMAE = 3 mm steel thickness.



Additional Notes

- Mild Steel quality S235JR/EN. Stainless Steel quality EN.14301/EN. Other steel qualities available upon request.
- For assembly of duct and fitting use clip or flange.
- To be welded on ductwork.
- Unpainted.

Compliance / Rating of Product Components

Product	Material	Compliance / Rating
Welded RMAD & RMAE adapter	Mild Steel	S235JR/EN

Temperature Rating of Product Components

	RMAD & RMAE Adapter
200°C	Mild Steel
-20°C	

