

TECHNICAL DATA SHEET: FB DUCT WITH ACCESS DOOR

Ø mm	Flat Edge mm	Length mm	Weight kg	Steel Thickness mm
80	6	500	0,9	0,7
100	6	500	1,1	0,7
120	6	500	1,2	0,7
125	6	500	1,3	0,7
140	6	500	1,4	0,7
150	6	500	1,5	0,7
160	6	500	1,5	0,7
180	6	500	1,7	0,7
200	6	500	1,8	0,7
225	6	500	2,0	0,7
250	6	500	2,3	0,7
300	6	500	2,7	0,7
315	6	500	3,9	0,7
350	6	500	4,0	0,9
400	6	500	4,6	0,9
450	6	500	5,3	0,9
500	6	500	5,7	0,9
550	6	500	6,3	0,9
600	6	500	7,4	0,9



Construction:

Longitudinal seam type: Laser (Ø80-500), above Ø500 is lockformed .

Ends: 6 mm turned out edge (FB).

Additional Notes

At temperatures ranging between 200° C and 250° C, the zinc-iron alloy layers in galvanised steel will continue to provide a high level of protection from corrosion. However, there may be some peeling, changes in mechanical properties, and reduction in the corrosion protection. All parts could be attached with cable for grounding. Recommended max. service temperature is +80°C.

Compliance / Rating of Product Components

Product	Material	Compliance / Rating
FB Duct with access door	Galvanised	DX51D with Z275 Coating

Temperature Rating of Product Components

	FB Duct with access door
200°C	Galvanised Steel
-20°C	

